

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
17 June 2004 (17.06.2004)

PCT

(10) International Publication Number
WO 2004/051372 A2

(51) International Patent Classification⁷: **G03F 7/00**

(21) International Application Number:
PCT/JP2003/015347

(22) International Filing Date: 1 December 2003 (01.12.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2002-350353 2 December 2002 (02.12.2002) JP

(71) Applicant (for all designated States except US): **TOKYO OHKA KOGYO CO., LTD.** [JP/JP]; 150, Nakamaruko, Nakahara-ku, Kawasaki-shi, Kanagawa 211-0012 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **HADA, Hideo** [JP/JP]; c/o Tokyo Ohka Kogyo Co., Ltd., 150, Nakamaruko, Nakahara-ku, Kawasaki-shi, Kanagawa 211-0012 (JP). **MIYAIRI, Miwa** [JP/JP]; c/o Tokyo Ohka Kogyo Co., Ltd., 150, Nakamaruko, Nakahara-ku, Kawasaki-shi, Kanagawa 211-0012 (JP). **KUBOTA, Naotaka** [JP/JP]; c/o Tokyo Ohka Kogyo Co., Ltd., 150, Nakamaruko, Nakahara-ku, Kawasaki-shi, Kanagawa 211-0012 (JP).

IWAI, Takeshi [JP/JP]; c/o Tokyo Ohka Kogyo Co., Ltd., 150, Nakamaruko, Nakahara-ku, Kawasaki-shi, Kanagawa 211-0012 (JP).

(74) Agents: **TANAI, Sumio** et al.; 2-3-1, Yaesu, Chuo-ku, Tokyo 104-8453 (JP).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report

[Continued on next page]

(54) Title: METHOD OF FORMING RESIST PATTERN, POSITIVE RESIST COMPOSITION, AND LAYERED PRODUCT



(57) Abstract: There are provided a method of forming a resist pattern that enables the resist pattern to be formed with good control of the pattern size, as well as a positive resist composition used in the method, and a layered product formed using the positive resist composition. In the above method a positive resist composition comprising a resin component (A), which contains a structural unit (a) derived from a (meth)acrylate ester represented by a general formula (I) shown below, and displays increased alkali solubility under action of acid, and an acid generator component (B) that generates acid on exposure is applied to a substrate, a prebake is conducted, the resist composition is selectively exposed, post exposure baking (PEB) is conducted, alkali developing is then used to form a resist pattern, and the pattern size of the thus produced resist pattern is then narrowed by heat treatment.

WO 2004/051372 A2



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.